


## Why choose KernowPrint FloorShark?

FloorShark™ is the only dry toner floor graphic rigorously tested and certified for slip resistance with a unique sharkskin coating. It's perfect for indoor environments, and can be applied to all smooth and hard floors, including low pile carpet tiles. Unlike other floor graphics, FloorShark™ doesn't shrink and there's no risk of the edge peeling or gumming up. Better yet, it's easy to remove – all in one piece and no residue.

Not only is FloorShark™ Dry Toner perfect for directing the flow of store traffic and reminding customers of social distancing, you can also take advantage of instant advertising – right on the floor. Customize floor graphics with your logo or sale items to keep customers “on-top” of your brand. A perfect combination for safe and reliable graphics that are easy to print and apply.



## Key Features

- Unique sharkskin coating – R10 certified
- Great printability – fast drying
- No need to laminate – print & apply
- No shrinkage & no dirty edges
- Resists heavy foot traffic – from heels to trucks
- Bfl-s1 and EN 13501 fire ratings



### UK, EU & RoW Product List

| PRODUCT DESCRIPTION                                             | SIZES             | PRODUCT CODE    |
|-----------------------------------------------------------------|-------------------|-----------------|
| 300µ KernowPrint (PET) FloorShark™ for Dry Toner                | SRA3              | 160HTFG         |
| 300µ KernowPrint (PET) FloorShark™ for Dry Toner Die-Cut Circle | A4 205mm circle   | 160HTFG.IC.A4   |
| 300µ KernowPrint (PET) FloorShark™ for Dry Toner Die-Cut Circle | SRA3 315mm circle | 160HTFG.IC.SRA3 |

### US Product List

| PRODUCT DESCRIPTION                                                | SIZES               | PRODUCT CODE |
|--------------------------------------------------------------------|---------------------|--------------|
| 7.1 mil KernowPrint (PET) FloorShark™ for Dry Toner                | SRA3                | P46          |
| 7.1 mil KernowPrint (PET) FloorShark™ for Dry Toner Die-Cut Circle | 8.5x11 6.8in circle | P46O         |



KERNOW  
COATINGS

KERNOWPRINT FLOORSHARK  
FOR DRY TONER





## KernowPrint FloorShark for Dry Toner (PET)

### Applications

- Indoor floor graphics
- Promotional graphics in supermarkets, shopping malls and retail outlets
- Directional or wayfinding floor signage
- Infographics in convention centers, schools, colleges and airports

### Compatibility

|                 |       |
|-----------------|-------|
| Laser Dry Toner | ★★★★★ |
| HP Indigo       | N/A   |
| Inkjet          | N/A   |
| Offset          | N/A   |

### Performance

|                     |                                   |
|---------------------|-----------------------------------|
| Overall Toughness   | ★★★★                              |
| Outdoor Use         | N/A                               |
| Heat Resistance     | ★★★★★                             |
| Chemical Resistance | ★★★                               |
| Rigidity            | ★★★★                              |
| Service Range       | -40°C to +255°C (-40°F to +491°F) |
| Adhesive            | Removable Solvent                 |

Tested for: **OKI intec xerox KONICA MINOLTA RICOH Kodak**

| Property                          | Typical Value           | Units  |
|-----------------------------------|-------------------------|--------|
|                                   | 160HTFG/P46             |        |
| Total Thickness                   | 300/11.8                | μ/mil  |
| Total Weight                      | 346                     | gsm    |
| Face Film Thickness (no adhesive) | 153                     | μ/mil  |
| Face Film Weight (no adhesive)    | 190                     | gsm    |
| Liner Thickness                   | 120                     | μ/mil  |
| Liner Weight                      | 130                     | gsm    |
| Adhesive Peel on Stainless Steel  | 8.5                     | N/25mm |
| Adhesive Application Temperature  | 5 to 50 / 41 to 122     | °C/°F  |
| Adhesive Service Temperature      | -40 to 180 / -40 to 356 | °C/°F  |



### Recommended conditions:

|                  |                           |              |
|------------------|---------------------------|--------------|
| <b>Printroom</b> | 10°C - 30°C (50°F - 86°F) | 40% - 55% RH |
| <b>Storage</b>   | 10°C - 20°C (50°F - 68°F) | 20% - 55% RH |

Please return unused product to its original packaging.  
Shelf Life: 24 months after delivery (under recommended storage conditions).

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted.  
We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.  
Regional certification differences apply.

Version 1, Copyright Sensitizers Group 2025

